

ADA Compliance Tip Sheet

Ten Common Accessibility Barriers & Solutions

1

Toilet inaccessible due to objects blocking side access.
Solution: Remove objects.

6

Grab bars are too high or at different heights.
Solution: Mount each grab bar at no higher than 34-36 inches to center of grab bar depending on height of toilet.

2

Bathroom signage should be on the wall of the latch-side of the door, **not on the door itself.**
Solution: Place signs on the latch-side of the door.

7

Toilets are too low.
Solution: Remove and install toilet to 17-19 inches high from finished floor or install lift to equal that same height range.

3

Access aisles for accessible parking are blocked by other cars, shopping carts, trash cans, etc.
Solution: Post No Parking signs and remove carts or barriers.

8

Mirrors, soap, and/or paper towels are too high.
Solution: Placement should be no more than 48 inches from finished floor to bottom of dispenser control or place items on sink surface.

4

Temporary barriers are placed in a way so as to **block access** in various areas such as plants, garbage cans, boxes, etc.
Solution: Remove barriers.

9

Doors are too heavy.
Solution: Adjust closer to 5 lbs maximum force needed to open the door.

5

Bathroom stalls too narrow.
Solution: Remove stall wall in adjoining toilet to create a larger stall.

10

No clear signage in the parking area **for accessible parking.**
Solution: Mount accessible parking signage on a pole in front of parking at a height of 60 inches from the ground to the bottom of the sign.

For more information:

Disability and Health Program at Alabama Department of Public Health www.adph.org/disability

Center for Emergency Preparedness at Alabama Department of Public Health www.adph.org/cep

Governor's Office on Disabilities www.good.alabama.gov

Alabama ADA Hotline 1-800-205-9986